Peelers Vegetable Peeler, 5kg with abrasive plate

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



601218 (T5S)

Vegetable Peeler, 5kg with abrasive plate 220-240V/1/50

Short Form Specification

Item No.

Constructed in stainless steel with a transparent removable lid in special high resistant plastic. The removable rotating plate is covered with a removable rotating plate covered in very resistant abrasive material (silicon carbide). An interlocking safety magnetic devices will stop the machine from operating when the lid or door is opened. The electronic controls and motor have IP55 protection. Simple control panel with ON/OFF buttons

Supplied with an abrasive plate.

Main Features

- Supplied with an abrasive plate as standard.
- Removable rotating plate covered in very resistant abrasive material (silicon carbide).
- Products downloading made easy thanks to the specific chute, activating manually the disc rotation to channel the product out of the peeling chamber.
- Magnetic detectors will stop the machine from operating when the lid and/or door are opened.
- Red OFF, green ON buttons and timer knob.
- Productivity suitable for 30-100 meals per service.

Construction

- Stainless steel construction with transparent lid in damage resistant plastic.
- IP55 waterproof control buttons.
- Transparent BPA free cover incorporates a magnetic safety system which stops the machine if lid is not properly closed.

Included Accessories

• 1 of Abrasive plate for 5 kg **PNC** vegetable peeler (T5S) 653182

Optional Accessories

• Filter table with sliding shelf

• Washing plate for 5 kg **PNC** vegetable peeler Abrasive plate for 5 kg vegetable peeler (T5S) Knife plate for 5 kg vegetable peeler (T5S)

653183 🗖 **PNC** 653784 🗖

653057 🗖

653182 🖵

PNC


PNC









Peelers Vegetable Peeler, 5kg with abrasive plate







Top

CWI1 = Cold Water inlet 1 D = Drain

Electrical inlet (power)

Electric Supply voltage:

601218 (T5S) 220-240 V/1N ph/50/60 Hz

Capacity:

Performance (up to): 80 - kg/hour

Capacity: 5 kg

Key Information:

External dimensions, Width: 314 mm
External dimensions, Height: 450 mm
External dimensions, Depth: 485 mm
Shipping weight: 21 kg

